

TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY



Telescoping frame & Shield Clamps
accommodate up to two shields
(sold separately)

TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY - LEVEL III

ARMOR SPECIFICATIONS:

Weight: 40.0 lbs.
Testing Standard: NIJ 0108.01
Protection Level: Level III & Special Threats
Plate Thickness: .56 in. / 14.22 mm
Materials: UHMWPE & Hybrid Ceramics
Cover: Black Polyurea

Threats: 5.56 x 45-mm, 55-grain M193 Ball
7.62 x 39-mm, 123-grain PS Ball
7.62 x 51-mm, 149-grain M80 FMJ
7.62 x 54R-mm, 148-grain LPS

TYR-RBS/BSD2-LV3

FEATURES & SPECIFICATIONS:

CONSTRUCTION

- Constructed out of high-strength, lightweight aluminum
- Two rubberized dolly handles
- Padded shield rest
- Center armor panel reinforces the connection area where the upper & lower shields meet
- Matte black powder coat finish

BALLISTIC COVERAGE

- Center armor panel covers the ballistic gap on both sides of the dolly
- Bolt holes on the armor panel are offset from the ballistic gap to reduce the possibility of penetration

FRAME ADJUSTABILITY

- Telescoping frame to accommodate up to two shields
- Telescoping, pull pin, shield handle bracket for multiple shield sizes

WHEEL CONFIGURATION

- Removable rear wheel
- Two-wheel configuration allows for 360° movement
- Dolly is self-supported in the two-wheel configuration by resting on the lower shield
- Three removable heavy duty wheels



TYR TACTICAL® PATENTED BALLISTIC SHIELD DOLLY



DOUBLE SHIELD:

The two-wheel configuration allows you to run the system as a ballistic barricade with 360° movement. Two handle heights allow the user to push the dolly in a standing or bowed position. The system can also tilt forward transforming it into a free-standing ballistic barricade.

11 PROVIDES BOTH LOAD CARRIAGE & UNMATCHED BALLISTIC PROTECTION. 11

11 SYSTEM DEPLOYS IN 90 SECONDS OR LESS 11

SINGLE SHIELD:

Provides a ballistic barricade in the tilt forward position. It also functions as a load carriage dolly for Broco O² Cylinders as well as mission specific MOLLE panels (sold separately).

